

Item	No.	Description	Price/Unit Euro	Total Euro
1		<p><b>m² roofing with FischerTRAPEZ-profiles</b>                      FI ..... as per DIN 18807, quality controlled                      sheet thickness: <input type="checkbox"/> 0.63 mm <input type="checkbox"/> 0,75 mm <input type="checkbox"/> 0.88 mm                                              <input type="checkbox"/> 1.00 mm <input type="checkbox"/> 1.25 mm <input type="checkbox"/> 1.50 mm                      supply length: ..... mm                      static system(s): .....span support                      span(s): .....m                      roof pitch: ..... degrees, ..... %                      end support width: ..... intermediate support width:  <input type="checkbox"/> ≥ 40 mm <input type="checkbox"/> ≥ 60 mm <input type="checkbox"/> ≥ 160 mm  <input type="checkbox"/> ..... mm <input type="checkbox"/> ≥ 120 mm <input type="checkbox"/> ..... mm                      max. deflection: <input type="checkbox"/> 1/150 <input type="checkbox"/> 1/.....                      Surface design:  <input type="checkbox"/> 55% AlZn AZ 185 (Aluzinc)  <input type="checkbox"/> Side B 200 µm HPS 200 colour..... /RSL                      or alternatively:  <input type="checkbox"/> Side B 25 µm SP colour..... /RSL  <input type="checkbox"/> Side B 25 µm PVF2 colour..... /RSL  <input type="checkbox"/> Side B, other: .....  <input type="checkbox"/> sealing of longitudinal joints (recommended up to roof pitch of 8°)  <input type="checkbox"/> sealing of end lap jointing, double  <input type="checkbox"/> fastening through the valley  <input type="checkbox"/> fastening through the crown  <input type="checkbox"/> fastening through the crown with spherical caps                      including delivery of all necessary fastening elements licensed by building authorities according to the static calculation, in accordance with side B on top on available substructure consisting of .....                      Delivery and mounting</p>		
2		<p><b>m² Fischer Kondensstop</b> as additional felt coating of the underside A of the FischerTRAPEZ-profiles of item 1 for the temporary buffering of condensation including the creation of non-absorbing areas in end lap joints using clear varnish.                      Additional charge</p>		
3		<p><b>m² shearing field formation</b> of roof surface areas of the FischerTRAPEZ-profiles as per overview drawing, load details and static calculation                      Additional charge</p>		
4		<p><b>m gable verge</b> consisting of  <b>gable verge flashing</b> <input type="checkbox"/> type 1 <input type="checkbox"/> type 2 <input type="checkbox"/> type 3                      strip galvanised steel sheet G 275                      sheet thickness: ..... mm cut to measure: ..... mm                      no. of bends: .....                      Surface design:  <input type="checkbox"/> Side A like outer skin of roof element  <input type="checkbox"/> Side A 200 µm HPS 200 colour..... /RSL  <input type="checkbox"/> Side A 25 µm SP colour..... /RSL  <input type="checkbox"/> Side A 25 µm PVF2 colour..... /RSL                      including suitable sealing between gable verge flashing and roof element and/or adjacent wall.                      (Order no. FI.....and/or as per sketch no. .......)                      including fastening material Delivery and mounting</p>		

Enquiry Form: Roofing with FischerTRAPEZ-Profiles

Item	No.	Description	Price/Unit Euro	Total Euro
5		<p><b>m ridge for gable roof</b>, consisting of  <b>ridge flashing</b> made of  strip galvanised steel sheet G 275  sheet thickness: 0.75 mm                      cut to measure: ..... mm  no. of bends: .....</p> <p>Surface design:  <input type="checkbox"/> Side A like outside of roof element      item .....</p> <p><input type="checkbox"/> Side A 200 µm HPS 200                      colour..... /RSL</p> <p><input type="checkbox"/> Side A 25 µm SP                                  colour..... /RSL</p> <p><input type="checkbox"/> 55% AlZn AZ 185 (Aluzinc)</p> <p>(Order no. Fl.....and/or as per sketch no. ....)</p> <p>including fastening material                      Delivery and mounting  and</p> <p><b>toothed flashing</b> made of  strip galvanised steel sheet G 275  sheet thickness: 0.75 mm                      cut to measure: ..... mm  no. of bends: .....</p> <p>Surface design:  <input type="checkbox"/> Side A like outer skin of roof element      item .....</p> <p><input type="checkbox"/> Side A 200 µm HPS 200                      colour..... /RSL</p> <p><input type="checkbox"/> Side A 25 µm SP                                  colour..... /RSL</p> <p><input type="checkbox"/> Side A 25 µm PVF2                      colour..... /RSL</p> <p><input type="checkbox"/> Side A, other: .....</p> <p>(Order no. Fl.....and/or as per sketch no. ....)</p> <p>including fastening material                      Delivery and mounting  and</p> <p><b>ridge flashing, inside</b>, made of  strip galvanised steel sheet G 275  sheet thickness: 0.75 mm                      cut to measure: ..... mm  no. of bends: .....</p> <p>Surface design:  <input type="checkbox"/> Side A like inside of roof element      item: .....</p> <p><input type="checkbox"/> Side A 200 µm HPS 200                      colour..... /RSL</p> <p><input type="checkbox"/> Side A 25 µm SP                                  colour..... /RSL</p> <p><input type="checkbox"/> 55% AlZn AZ 185 (Aluzinc)</p> <p>(Order no. Fl.....and/or as per sketch no. ....)</p> <p>including fastening material                      Delivery and mounting</p>		

Item	No.	Description	Price/Unit Euro	Total Euro
6		<p><b>m ridge capping, type B</b> made of strip galvanised steel sheet G 275 FischerTRAPEZ-profiles  <input type="checkbox"/> 35/207    <input type="checkbox"/> 40/183    <input type="checkbox"/> 50/250                      sheet thickness:  <input type="checkbox"/> 0.75 mm    <input type="checkbox"/> 0.88 mm    <input type="checkbox"/> 1.00 mm    cut to measure: .....mm                      Surface treatment:  <input type="checkbox"/> Side B, roof elements  <input type="checkbox"/> Side B 200 µm HPS 200                      colour..... /RSL  <input type="checkbox"/> Side B 25 µm SP                                      colour..... /RSL                      each with two sealing strips on both sides of the ridge                      side length approx. 250 mm                      (Order no. FI.....and/or as per sketch no. ....)                      including fastening material                                      Delivery and mounting</p>		
7		<p><b>m ridge for monopitch roof</b>, consisting of <b>ridge flashing for monopitch roof</b> made of strip galvanised steel sheet G 275 sheet thickness: 0.75 mm                      cut to measure: ..... mm no. of bends: .....</p> <p>Surface design:  <input type="checkbox"/> Side A like outside of roof element              item .....</p> <p><input type="checkbox"/> Side A 200 µm HPS 200                      colour..... /RSL  <input type="checkbox"/> Side A 25 µm SP                                      colour..... /RSL                      (Order no. FI.....and/or as per sketch no. ....)                      including bending up the valleys of the FischerTRAPEZ-profiles                      including fastening material                                      Delivery and mounting                      and</p> <p><b>toothed flashing</b> made of strip galvanised steel sheet G 275 sheet thickness: 0.75 mm                      cut to measure: ..... mm no. of bends: .....</p> <p>Surface design:  <input type="checkbox"/> Side A like outside of roof element              item .....</p> <p><input type="checkbox"/> Side A 200 µm HPS 200                      colour..... /RSL  <input type="checkbox"/> Side A 25 µm SP                                      colour..... /RSL  <input type="checkbox"/> Side A, other: .....</p> <p>(Order no. FI.....and/or as per sketch no. ....)                      including fastening material                                      Delivery and mounting</p>		

## Enquiry Form: Roofing with FischerTRAPEZ-Profiles

Item	No.	Description	Price/Unit Euro	Total Euro
8		<p><b>m ventilation ridge</b> consisting of  <b>tie beam flashing</b> made of  strip galvanised steel sheet G 275  sheet thickness: 1.00 mm                              cut to measure: ..... mm  no. of bends: .....  Surface design:  <input type="checkbox"/> Side A like outside of roof element              item .....</p> <p><input type="checkbox"/> Side A 25 µm SP    colour..... /RSL  <input type="checkbox"/> Side A spray painted    colour..... /RSL  <input type="checkbox"/> Side A, other: .....</p> <p>(Order no. Fl.....and/or as per sketch no. ....)</p> <p>including fastening material  and</p> <p><b>pc. brackets (2 pcs. / m)</b> made of  strip galvanised steel sheet G 275  sheet thickness: 1.50 mm                              cut to measure: ..... mm  no. of bends: .....  Surface design:  <input type="checkbox"/> Side A like outside of roof element              item .....</p> <p><input type="checkbox"/> Side A 25 µm SP    colour..... /RSL  <input type="checkbox"/> Side A, other: .....</p> <p>(Order no. Fl.....and/or as per sketch no. ....)</p> <p>including fastening material  and</p> <p><b>ventilation dome</b> made of  strip galvanised steel sheet G 275  sheet thickness: 1.00 mm                              cut to measure: ..... mm  no. of bends: .....  Surface design:  <input type="checkbox"/> Side A like outside of roof element  <input type="checkbox"/> Side A 25 µm SP    colour..... /RSL  <input type="checkbox"/> Side A spray painted    colour..... /RSL  <input type="checkbox"/> Side A, other: .....</p> <p>(Order no. Fl.....and/or as per sketch no. ....)</p> <p>including fastening material  and</p> <p><b>toothed flashing</b> made of  strip galvanised steel sheet G 275  sheet thickness: 0.75 mm                              cut to measure: ..... mm  no. of bends: .....  Surface design:  <input type="checkbox"/> Side A like outside of roof element  <input type="checkbox"/> Side A 200 µm HPS 200    colour..... /RSL  <input type="checkbox"/> Side A 25 µm SP    colour..... /RSL  <input type="checkbox"/> Side A, other: .....</p> <p>(Order no. Fl.....and/or as per sketch no. ....)</p> <p>including bending up both sides of the valleys of the FischerTRAPEZ-profiles  including fastening material    Delivery and mounting</p>		

Item	No.	Description	Price/Unit Euro	Total Euro
9		<p><b>m roof-wall connection</b> on ridge of monopitch roof, <b>across</b> the laying direction of the FischerTRAPEZ-profiles consisting of:</p> <p><b>wall connection flashing</b> manufactured from strip galvanised steel sheet G 275 sheet thickness: 0.75 mm                              cut to measure: ..... mm no. of bends: .....</p> <p>Surface design: <input type="checkbox"/> Side A like outside of roof element <input type="checkbox"/> Side A 200 µm HPS 200                              colour..... /RSL <input type="checkbox"/> Side A 25 µm SP    colour..... /RSL <input type="checkbox"/> Side A, other: .....</p> <p>(Order no. FI.....and/or as per sketch no. ....)</p> <p>including fastening material and</p> <p><b>toothed flashing</b> made of strip galvanised steel sheet G 275 sheet thickness: 0.75 mm                              cut to measure: ..... mm no. of bends: .....</p> <p>Surface design: <input type="checkbox"/> Side A like outside of roof element <input type="checkbox"/> Side A 200 µm HPS 200                              colour..... /RSL <input type="checkbox"/> Side A 25 µm SP    colour..... /RSL <input type="checkbox"/> Side A, other: .....</p> <p>(Order no. FI.....and/or as per sketch no. ....)</p> <p>including bending up the valleys of the FischerTRAPEZ-profiles including fastening material                              Delivery and mounting</p>		
10		<p><b>m roof-wall connection</b> on ridge of monopitch roof, <b>along</b> the laying direction of the FischerTRAPEZ-profiles consisting of:</p> <p><b>wall connection flashing</b> manufactured from strip galvanised steel sheet G 275 sheet thickness: 0.75 mm                              cut to measure: ..... mm no. of bends: .....</p> <p>Surface design: <input type="checkbox"/> Side A like outside of roof element <input type="checkbox"/> Side A 200 µm HPS 200                              colour..... /RSL <input type="checkbox"/> Side A 25 µm SP    colour..... /RSL <input type="checkbox"/> Side A, other: .....</p> <p>(Order no. FI.....and/or as per sketch no. ....)</p> <p>including fastening material                              Delivery and mounting</p>		
11		<p><b>m adapting</b> the roof-wall connection flashing to the pitch of the roof Additional charge</p>		

**Enquiry Form: Roofing with FischerTRAPEZ-Profiles**

Item	No.	Description	Price/Unit Euro	Total Euro
12		<p><b>m wall connection flashing</b> for connection to rising wall components, made of strip galvanised steel sheet G 275  <input type="checkbox"/> type 1 <input type="checkbox"/> type 2 <input type="checkbox"/> type 3                      sheet thickness: ..... mm cut to measure: ..... mm                      no. of bends: .....                      Surface design:  <input type="checkbox"/> Side A like outside of roof element item .....  <input type="checkbox"/> Side A 200 µm HPS 200 colour..... /RSL  <input type="checkbox"/> Side A 25 µm SP colour..... /RSL  <input type="checkbox"/> Side A 25 µm PVF2 colour..... /RSL  <input type="checkbox"/> Side A, other: .....                      (Order no. Fl.....and/or as per sketch no. ....)                      including sealing to the wall surface with permanently elastic, closed cell silicon sealant                      including fastening material Delivery and mounting</p>		
13		<p><b>m gutter flashing</b>, made of strip galvanised steel sheet G 275                      sheet thickness: 0.75 mm cut to measure: ..... mm                      no. of bends: .....                      Surface design:  <input type="checkbox"/> Side A like outside of roof element item .....  <input type="checkbox"/> Side A 200 µm HPS 200 colour..... /RSL  <input type="checkbox"/> Side A 25 µm SP colour..... /RSL  <input type="checkbox"/> Side A 25 µm PVF2 colour..... /RSL  <input type="checkbox"/> 55% AlZn AZ 185 (Aluzinc)                      (Order no. Fl.....and/or as per sketch no. ....)                      including fastening material Delivery and mounting</p>		
14		<p><b>m snow flashing</b>, made of strip galvanised steel sheet G 275                      sheet thickness: <input type="checkbox"/> 0.75 mm <input type="checkbox"/> 1.00 mm <input type="checkbox"/> 1.50 mm                      cut to measure: ..... mm                      no. of bends: .....                      Surface design:  <input type="checkbox"/> Side A like outside of roof element item .....  <input type="checkbox"/> Side A 200 µm HPS 200 colour..... /RSL  <input type="checkbox"/> Side A 25 µm SP colour..... /RSL  <input type="checkbox"/> Side A 25 µm PVF2 colour..... /RSL  <input type="checkbox"/> 55 % AlZn AZ 185 (Aluzinc)                      (Order no. Fl.....and/or as per sketch no. ....)                      including fastening material                      and</p>		

Item	No.	Description	Price/Unit Euro	Total Euro
		<p><b>m bracket for snow flashing</b>, made of strip galvanised steel sheet G 275 sheet thickness: 1.50 mm cut to measure: ..... mm no. of bends: .....</p> <p>Surface design:  <input type="checkbox"/> Side A like outside of roof element item .....  <input type="checkbox"/> Side A 25 µm SP colour..... /RSL  <input type="checkbox"/> 55 % AlZn AZ 185 (Aluzinc)                      (Order no. FI 20.265)                      including fastening material Delivery and mounting</p>		
15		<p><b>pc. cutting</b> of a roof aperture Length in direction of profile: .....m Length across direction of profile: .....m performed with suitable cutting tools with no flying sparks Additional charge</p>		
16		<p><b>pc. crown, single-skin</b>, with suitable flanges, for the FischerTRAPEZ-profiles roof element for fixing  <input type="checkbox"/> skylights, make:.....  <input type="checkbox"/> smoke and heat extractor systems, make:.....  <input type="checkbox"/> ventilators, make:.....  <input type="checkbox"/> exit openings in roof, make:.....</p> <p>Material:  <input type="checkbox"/> aluminium  <input type="checkbox"/> .....</p> <p>surface:  <input type="checkbox"/> inside similar to RAL.....  <input type="checkbox"/> outside similar to RAL.....  <input type="checkbox"/> natural aluminium                      crown height: <input type="checkbox"/> 150 mm <input type="checkbox"/> 300 mm <input type="checkbox"/> ..... mm                      Nominal size ..... m x ..... m                      (Order no. FI.....)                      including fastening elements Delivery and mounting</p>		
17		<p><b>pc. crown, for chimney</b>, with suitable flanges, for the FischerTRAPEZ-profiles roof elements                      including chimney connector and overhang flashing fastened to the chimney and sealed                      chimney dimensions: ..... mm x ..... mm                      height : <input type="checkbox"/> 300 mm <input type="checkbox"/> ..... mm                      (construction as per sketch no.: .....)                      including fastening elements Delivery and mounting</p>		

Enquiry Form: Roofing with FischerTRAPEZ-Profiles

Item	No.	Description	Price/Unit Euro	Total Euro
18		<p><b>m cover plate</b> (sliding plate) from the ridge as a connecting plate to roof penetrations for ventilation pipes, chimneys, apertures, etc. made of strip galvanised steel sheet G 275                      sheet thickness: .....mm                      cut to measure: .....mm                      no. of bends: .....</p> <p>Surface treatment:  <input type="checkbox"/> Side A like outside of roof element            item .....</p> <p><input type="checkbox"/> Side A 200 µm HPS 200                          colour..... /RSL</p> <p><input type="checkbox"/> Side A 25 µm SP    colour..... /RSL</p> <p><input type="checkbox"/> Side A 25 µm PVF2                                      colour..... /RSL</p> <p><input type="checkbox"/> 55%AlZn AZ185 (Aluzinc)</p> <p>The hollow space between the roof panel and the cover plate must be filled without gaps with mineral fibre insulation.                      (construction as per sketch no.: .....)</p> <p>including fastening elements                      Delivery and mounting</p>		
19		<p><b>m<sup>2</sup> light panels</b> for FischerTRAPEZ-profiles  <input type="checkbox"/> FI 35/207   <input type="checkbox"/> FI 40/183   <input type="checkbox"/> FI 50/250                      material:  <input type="checkbox"/> polyvinyl chloride (PVC) 1.5 mm thick  <input type="checkbox"/> polyester, glass fibre reinforced (GFK) 1.0 mm thick  <input type="checkbox"/> polycarbonate (PC) 1.0 mm thick                      with max. purlin spacing of ..... m                      (order no.: .....)</p> <p>including suitable fastening material                      Delivery and mounting</p>		
20		<p><b>pc. sliding substructure</b> for compensating for thermal expansion of the light plates, consisting of profiled main girders mounted between the available purlins and sliding subsidiary girders as support for the light plates.                      (as per sketch no.: .....)</p> <p>including fastening elements                      Delivery and mounting</p>		
21		<p><b>m cover plate</b> made of strip galvanised steel sheet G 275                      sheet thickness: .....mm                      cut to measure: .....mm                      no. of bends: .....</p> <p>for the sliding, unconnected longitudinal lap jointing                      FischerTRAPEZ-profiles / light plates</p> <p>Surface treatment:  <input type="checkbox"/> Side A like outside of roof element            item .....</p> <p><input type="checkbox"/> Side A 200 µm HPS 200                          colour..... /RSL</p> <p><input type="checkbox"/> Side A 25 µm SP    colour..... /RSL</p> <p><input type="checkbox"/> Side A other: .....    colour..... /RSL</p> <p>(Order no. FI.....and/or as per sketch no. ....)</p> <p>including fastening elements                      Delivery and mounting</p>		



Item	No.	Description	Price/Unit Euro	Total Euro
22		<b>pc. opening for pipes, type EJOT® „FLASH“</b> , max. 305 mm outer flange dimension, for max. 230 mm pipe diameter including producing the opening in the metal sheet with snips or nibbler and sealing with Ejoplast joint sealant with the fixing of the supplied screws in the valley. (order no. FI.....) Delivery and mounting		
23		<b>m special flashing</b> for ..... made of strip galvanised steel sheet G 275 sheet thickness: .....mm cut to measure: .....mm no. of bends: ..... Surface treatment: <input type="checkbox"/> Side A like outside of roof panel <input type="checkbox"/> Side A 200 µm HPS 200 colour..... /RSL <input type="checkbox"/> Side A 25 µm SP colour..... /RSL <input type="checkbox"/> 55%AlZn AZ185 (Aluzinc) <input type="checkbox"/> Other ..... (as per sketch no. ....) including fastening material Delivery and mounting		
24		<b>m cutting</b> the FischerTRAPEZ-profiles on the building site <input type="checkbox"/> longitudinal cutting <input type="checkbox"/> traverse cutting <input type="checkbox"/> diagonal cutting with suitable cutting tools without flying sparks Additional charge		
25		<b>m profile filler</b> , suitable for FischerTRAPEZ-profiles FI ....., <b>lower skin</b> , made of <input type="checkbox"/> closed-cell polyethylene foam, thickness 30 mm <input type="checkbox"/> closed-cell EPDM foam <input type="checkbox"/> non-combustible material for <input type="checkbox"/> small profiled rib <input type="checkbox"/> large profiled rib, as <input type="checkbox"/> separate pieces <input type="checkbox"/> profile filler strip (order no. FI .....) Delivery and mounting		
26		<b>m profile filler</b> , suitable for FischerTRAPEZ-profiles FI ....., <b>upper skin</b> , made of <input type="checkbox"/> closed-cell polyethylene foam, thickness 30 mm <input type="checkbox"/> closed-cell EPDM foam <input type="checkbox"/> small profiled rib <input type="checkbox"/> large profiled rib, as <input type="checkbox"/> separate pieces <input type="checkbox"/> profile filler strip (order no. FI .....) Delivery and mounting		
27		<b>m sealing strip</b> illac 20 x 4 (order no. FI 81.003) Additional charge		

Please tick as appropriate

## Enquiry Form: Roofing with FischerTRAPEZ-Profiles

Item	No.	Description	Price/Unit Euro	Total Euro
28		<b>m compressed sealing strip</b> illmod SFI 30 x 6-16 (order no. FI 81.001) <div style="text-align: right;">Additional charge</div>		
29		<b>pc. self-sealing screw</b> made of stainless steel type: ..... (order no. FI.....) <div style="text-align: right;">Additional charge</div>		
30		<b>pc. drilling screw</b> made of stainless steel type: ..... (order no. FI.....) <div style="text-align: right;">Additional charge</div>		
31		<b>pc. blind rivet</b> made of aluminium/stainless steel type: ..... (order no. FI.....) <div style="text-align: right;">Additional charge</div>		
32		<b>pc. EJOT® ORKAN spherical caps</b> for fastening in the crown FischerTRAPEZ-profiles: <input type="checkbox"/> 35/207 <input type="checkbox"/> 40/183 <input type="checkbox"/> 50/250 Surface treatment: <input type="checkbox"/> Aluminium <input type="checkbox"/> polished <input type="checkbox"/> coated                    colour..... (order no. FI.....) <div style="text-align: right;">Additional charge</div>		
33		<b>Static calculation</b> as per DIN 18807 including static proof of the joints in the roof opening areas and the connections of the profiled sheets, in triplicate. <div style="text-align: right;">Flat rate</div>		
34		<b>Laying plans</b> according to the requirements of DIN 18807 Part 3 and the regulations of the IFBS, in triplicate <div style="text-align: right;">Flat rate</div>		
35		<b>hrs. hourly wage work</b> chief erecting engineer		
36		<b>hrs. hourly wage work</b> skilled erector		
37		<b>hrs. hourly wage work</b> unskilled erector		
38		<b>interruptions on the building</b> site flat rate		
		<b>Net total + VAT</b>		

A large, empty rectangular box with a thin black border, intended for the user to provide details for their enquiry.