

| Item | No. | Description | Price/Unit Euro | Total Euro |
|------|-----|---|--------------------|---------------|
| 1 | | <p>m² FischerTHERM composite wall cladding panels, consisting of a core of polyurethane (PUR) rigid foam (CFC and HCFC-free) between decking skins made of strip galvanised or strip alloy galvanised and additionally polyester coated steel sheet. The longitudinal jointing is factory-fitted with a soft, filling sealing strip (thermal insulation) and additionally with an EPDM sealing profile (air-tightness). This guarantees extraordinarily tight joints.</p> <p>a-value = approx. 0.02 m³/h · m(10 Pa)^{2/3}</p> <p>Fischer ISOTHERM construction elements are licensed by building authorities and quality controlled.</p> <p>Element type:</p> <p>FischerTHERM <input type="checkbox"/> LL 40 <input type="checkbox"/> LL60 <input type="checkbox"/> LL80 <input type="checkbox"/> LL100 FischerTHERM <input type="checkbox"/> ML 40 <input type="checkbox"/> ML60 <input type="checkbox"/> ML80 <input type="checkbox"/> ML100</p> <p>construction width 1100 mm <input type="checkbox"/> Special construction width 1000 mm</p> <p>Sheet thickness outer skin: <input type="checkbox"/> 0.55 mm Sheet thickness inner skin: <input type="checkbox"/> 0.40 mm <input type="checkbox"/> 0.55 mm Supply length: mm</p> <p>Element type:</p> <p>FischerTHERM plus <input type="checkbox"/> SL 60 <input type="checkbox"/> SL80 <input type="checkbox"/> SL100 FischerTHERM plus <input type="checkbox"/> ML 60 <input type="checkbox"/> ML80 <input type="checkbox"/> ML100 FischerTHERM plus <input type="checkbox"/> KL 60 <input type="checkbox"/> KL80 <input type="checkbox"/> KL100</p> <p>construction width 1000 mm Sheet thickness outer skin: <input type="checkbox"/> 0.63 mm Sheet thickness inner skin: <input type="checkbox"/> 0.55 mm Supply length mm <input type="checkbox"/> incl. load distributors in the 2m corner area <input type="checkbox"/> incl. load distributors over total area</p> <p>Element type:</p> <p>FischerTHERM TL <input type="checkbox"/> TL 65 <input type="checkbox"/> TL 85</p> <p>construction width 1000 mm Sheet thickness outer skin: <input type="checkbox"/> 0.55 mm <input type="checkbox"/> 0.63 mm Sheet thickness inner skin: <input type="checkbox"/> 0.55 mm Supply length mm</p> <p>Element type:</p> <p>FischerTHERM WL <input type="checkbox"/> WL 80 <input type="checkbox"/> WL 100</p> <p>construction width 1000 mm Sheet thickness outer skin: <input type="checkbox"/> 0,63 mm Sheet thickness inner skin: <input type="checkbox"/> 0,55 mm Supply length: mm</p> <p>Heat transition coefficient k-value: [W/(m²K)] Air permeability of joints a-value = approx. 0 m³/h · m(10 Pa)^{2/3}</p> <p>Laying: <input type="checkbox"/> vertical <input type="checkbox"/> horizontal <input type="checkbox"/> diagonal,perpendicular</p> <p>Height of wall:m, element length max:.....m</p> | | |

Please tick as appropriate

Enquiry Form for FischerTHERM wall

| Item | No. | Description | Price/Unit Euro | Total Euro |
|------|-----|--|-----------------|------------|
| | | <p>Rail design: <input type="checkbox"/> steel <input type="checkbox"/> C-profile type: <input type="checkbox"/> Z-profile type: <input type="checkbox"/> wood <input type="checkbox"/> reinforced concrete with embedded fixing rail, Type: static system(s):span support span(s):m cantilever length.....m end support width: <input type="checkbox"/> mm intermediate support width: <input type="checkbox"/> mm max. deflection: <input type="checkbox"/> l/150 <input type="checkbox"/> l/.....</p> <p>Surface design: <input type="checkbox"/> Outer skin 200 µm HPS 200 colour..... /RSL <input type="checkbox"/> Outer skin 25 µm SP colour..... /RSL <input type="checkbox"/> Outer skin 25 µm PVF2 colour..... /RSL <input type="checkbox"/> Outer skin, other:..... <input type="checkbox"/> Inner skin 12 µm SP, colour similar to RAL 9002 <input type="checkbox"/> Inner skin, other:.....</p> <p>including delivery of all necessary fastening elements licensed by building authorities according to the static calculation, in accordance with the specialist rules of the IFBS.</p> <p style="text-align: right;">Delivery and mounting</p> | | |
| 2 | | <p>m² additional charge for partial surfaces with profile lengths ≤ 2.0 m Additional charge</p> | | |
| 3 | | <p>m drip flashing for bottom edge of wall and horizontal joint made of strip galvanised steel sheet G 275 sheet thickness: 0.75 mm cut to measure: mm no. of bends:</p> <p>Surface design: <input type="checkbox"/> Side A like FischerTHERM item: <input type="checkbox"/> Side A 200 µm HPS 200 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm SP <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm PVF2 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A, other:.....</p> <p>(Order no. Fl.....and/or as per sketch no.)</p> <p>including fastening material Delivery and mounting</p> | | |
| 4 | | <p>m horizontal flashing made of strip galvanised steel sheet G 275 sheet thickness: 0.75 mm cut to measure: mm no. of bends:</p> <p>Surface design: <input type="checkbox"/> Side A like FischerTHERM item: <input type="checkbox"/> Side A 200 µm HPS 200 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm SP <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm PVF2 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A, other:.....</p> <p>(Order no. Fl.....and/or as per sketch no.)</p> <p>including fastening material Delivery and mounting</p> | | |

| Item | No. | Description | Price/Unit Euro | Total Euro |
|------|-----|--|--------------------|---------------|
| 5 | | <p>m outer corner profile made of strip galvanised steel sheet G 275 type: sheet thickness: 0.75 mm cut to measure: mm no. of bends: Surface design: <input type="checkbox"/> Side A like FischerTHERM item: <input type="checkbox"/> Side A 200 µm HPS 200 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm SP <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm PVF2 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A, other:..... (Order no. Fl.....and/or as per sketch no.) including fastening material Delivery and mounting</p> | | |
| 6 | | <p>m inner corner profile made of strip galvanised steel sheet G 275 type: sheet thickness: 0.75 mm cut to measure: mm no. of bends: Surface design: <input type="checkbox"/> Side A like FischerTHERM item: <input type="checkbox"/> Side A 200 µm HPS 200 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm SP <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm PVF2 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A, other:..... (Order no. Fl.....and/or as per sketch no.) including fastening material Delivery and mounting</p> | | |
| 7 | | <p>m angle support made of strip galvanised steel sheet G 275 sheet thickness: 1.50 mm cut to measure: mm no. of bends: Surface design: <input type="checkbox"/> Side A 25 µm SP, colour..... /RSL <input type="checkbox"/> 55%AlZn AZ 185 (Aluzinc) (Order no. Fl.....and/or as per sketch no.) including fastening material Delivery and mounting</p> | | |
| 8 | | <p>m substructure angle for FischerTHERM plus made of strip galvanised steel sheet G 275 sheet thickness: 1.50 mm cut to measure: mm no. of bends: Surface design: <input type="checkbox"/> Side A 25 µm SP, colour..... /RSL <input type="checkbox"/> 55%AlZn AZ 185 (Aluzinc) (Order no. Fl.....and/or as per sketch no.) including fastening material Delivery and mounting</p> | | |

Please tick as appropriate

| Item | No. | Description | Price/Unit Euro | Total Euro |
|------|-----|--|--------------------|---------------|
| 12 | | <p>m verge flashing, consisting of verge flashing support, made of strip galvanised steel sheet G 275 sheet thickness: 1.00 mm cut to measure: mm no. of bends:</p> <p>Surface design: <input type="checkbox"/> Side A 25 µm SP, colour..... /RSL <input type="checkbox"/> 55%AlZn AZ 185 (Aluzinc) (Order no. FI.....and/or as per sketch no.)</p> <p>including fastening material Delivery and mounting and</p> <p>verge capping, made of strip galvanised steel sheet G 275 sheet thickness: 0.75 mm cut to measure: mm no. of bends:</p> <p>Surface design: <input type="checkbox"/> Side A like FischerTHERM item: <input type="checkbox"/> Side A 200 µm HPS 200 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm SP <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm PVF2 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A, other:.....</p> <p>(Order no. FI.....and/or as per sketch no.)</p> <p>including fastening material Delivery and mounting</p> | | |
| 13 | | <p>pc. load distributor for FischerTHERM plus sheet thickness: 1.50 mm Surface design: <input type="checkbox"/> 55%AlZn AZ 185 (Aluzinc) (Order no. FI 91.030)</p> <p style="text-align: right;">Delivery and mounting</p> | | |
| 14 | | <p>m special edge flashing for</p> <p>.....made of strip galvanised steel sheet G 275 sheet thickness: mm cut to measure: mm no. of bends:</p> <p>Surface design: <input type="checkbox"/> Side A like FischerTHERM item: <input type="checkbox"/> Side A 200 µm HPS 200 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm SP <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A 25 µm PVF2 <input type="checkbox"/> colour..... /RSL <input type="checkbox"/> Side A, other:.....</p> <p>(as per sketch no.)</p> <p>including fastening material Delivery and mounting</p> | | |

Enquiry Form for FischerTHERM wall

| Item | No. | Description | Price/Unit Euro | Total Euro |
|------|-----|---|-----------------|------------|
| 15 | | <p>m support profile type 1 for horizontally laid FischerTHERM wall cladding elements</p> <p style="text-align: center;"> <input type="checkbox"/> WL 80 <input type="checkbox"/> WL 100 <input type="checkbox"/> plus 60 <input type="checkbox"/> plus 80 <input type="checkbox"/> plus 100 </p> <p>made of strip galvanised steel sheet G 275 sheet thickness: 1.50 mm cut to measure: mm no. of bends:</p> <p>Surface design: <input type="checkbox"/> Side A 25 µm SP, colour..... /RSL <input type="checkbox"/> 55%AlZn AZ 185 (Aluzinc) (Order no. FI 85.065) including fastening material Delivery and mounting</p> | | |
| 16 | | <p>m support profile type 2 for horizontally laid FischerTHERM wall cladding elements</p> <p style="text-align: center;"> <input type="checkbox"/> WL 80 <input type="checkbox"/> WL 100 <input type="checkbox"/> plus 60 <input type="checkbox"/> plus 80 <input type="checkbox"/> plus 100 </p> <p>made of strip galvanised steel sheet G 275 sheet thickness: 1.50 mm cut to measure: mm no. of bends:</p> <p>Surface design: <input type="checkbox"/> Side A 2 5 µm SP, colour..... /RSL <input type="checkbox"/> 55%AlZn AZ 185 (Aluzinc) (Order no. FI 85.066) including fastening material Delivery and mounting</p> | | |
| 17 | | <p>m aluminium edge pilaster strip for horizontally laid FischerTHERM wall cladding elements</p> <p style="text-align: center;"> <input type="checkbox"/> WL 80 <input type="checkbox"/> WL 100 sheet thickness: 3.00 mm cut to measure: mm Surface design: <input type="checkbox"/> powder coated colour..... /RSL <input type="checkbox"/> PURAC coating colour..... /RSL (Order no. FI 85.064) including fastening material Delivery and mounting</p> | | |
| 18 | | <p>m aluminium pilaster strip type 1 for horizontally laid FischerTHERM wall cladding elements</p> <p style="text-align: center;"> <input type="checkbox"/> WL 80 <input type="checkbox"/> WL 100 <input type="checkbox"/> plus 60 <input type="checkbox"/> plus 80 <input type="checkbox"/> plus 100 </p> <p>Surface design: <input type="checkbox"/> anodised <input type="checkbox"/> powder coated colour..... /RSL <input type="checkbox"/> PURAC coating colour..... /RSL (Order no. FI 85.060) including fastening material Delivery and mounting</p> | | |

| Item | No. | Description | Price/Unit Euro | Total Euro |
|------|-----|---|--------------------|---------------|
| 19 | | <p>m aluminium pilaster strip type 2 for horizontally laid FischerTHERM wall cladding elements</p> <p><input type="checkbox"/> WL 80 <input type="checkbox"/> WL 100</p> <p><input type="checkbox"/> plus 60 <input type="checkbox"/> plus 80 <input type="checkbox"/> plus 100</p> <p>Surface design:</p> <p><input type="checkbox"/> anodised</p> <p><input type="checkbox"/> powder coated colour..... /RSL</p> <p><input type="checkbox"/> PURAC coating colour..... /RSL</p> <p>(Order no. FI 85.061)</p> <p>including fastening material Delivery and mounting</p> | | |
| 20 | | <p>m aluminium cover strip type 2 to match aluminium pilaster strip type 1</p> <p>Surface design:</p> <p><input type="checkbox"/> anodised</p> <p><input type="checkbox"/> powder coated colour..... /RSL</p> <p><input type="checkbox"/> PURAC coating colour..... /RSL</p> <p>(Order no. FI 85.063)</p> <p>Delivery and mounting</p> | | |
| 21 | | <p>m aluminium cover strip type 1 to match aluminium pilaster strip type 2</p> <p>Surface design:</p> <p><input type="checkbox"/> anodised</p> <p><input type="checkbox"/> powder coated colour..... /RSL</p> <p><input type="checkbox"/> PURAC coating colour..... /RSL</p> <p>(Order no. FI 85.062)</p> <p>Delivery and mounting</p> | | |
| 22 | | <p>m DUO sealant for horizontally laid FischerTHERM wall cladding elements</p> <p><input type="checkbox"/> WL 80 <input type="checkbox"/> WL 100</p> <p><input type="checkbox"/> plus 60 <input type="checkbox"/> plus 80 <input type="checkbox"/> plus 100</p> <p>(Order no. FI)</p> <p>including fastening material Delivery and mounting</p> | | |
| | | | | |

| Item | No. | Description | Price/Unit Euro | Total Euro |
|------|-----|--|--------------------|---------------|
| 25 | | m cutting on the building site <input type="checkbox"/> longitudinal cutting <input type="checkbox"/> traverse cutting <input type="checkbox"/> diagonal cutting with suitable cutting tools without flying sparks Additional charge | | |
| 26 | | pc. wall aperture at the building site, for dimensions: length: mm, width mm Ø mm with suitable cutting tools without flying sparks Additional charge | | |
| 27 | | m sealing strip illac 20 x 4 (order no. FI 81.003) Additional charge | | |
| 28 | | m compressed sealing strip illmod SFI 30 x 6-16 (order no. FI 81.001) Additional charge | | |
| 29 | | pc. self-sealing screw made of stainless steel type: (order no. FI.....) Additional charge | | |
| 30 | | pc. drilling screw made of stainless steel type: (order no. FI.....) Additional charge | | |
| 31 | | pc. blind rivet made of aluminium/stainless steel type: (order no. FI.....) Additional charge | | |
| 32 | | Static calculation as per DIN 18807 including the connections of the profiled elements to the substructure, in triplicate. Flat rate | | |
| 33 | | Laying plans according to the requirements of DIN 18807 Part 3, in triplicate Flat rate | | |
| 34 | | hrs. hourly wage work chief erecting engineer | | |
| 35 | | hrs. hourly wage work skilled erector | | |
| 36 | | hrs. hourly wage work unskilled erector | | |
| 37 | | interruptions on the building site flat rate | | |
| | | Net total + VAT | | |

Please tick as appropriate

