

Item	No.	Description	Price/Unit Euro	Total Euro
1		<p>m² safety net as per DIN EN 1263-1 „Safety nets and accessories for safety nets“ according to the safety regulations „Safety Nets“ (ZH 1/560), installation, fastening of the safety nets to suspension arrangements provided on site by the customer to construction components made of</p> <p><input type="checkbox"/> steel <input type="checkbox"/> concrete <input type="checkbox"/> wood <input type="checkbox"/></p> <p>Keeping the installation height of the net m above the bay floor for the duration of the roof assembly work and then removing it, below a total surface area of m² The floor of the bay is accessible and useable for vertical lifts.</p>		
2		<p>m² safety net as previously described item but only below unconnected areas of approx. m² installation including slings</p> <p style="text-align: right;">unit price</p>		
3		<p>m² safety net as previously described item, keeping in place for the agreed duration, pro week begun</p> <p style="text-align: right;">unit price</p>		
4		<p>pc. fall protection from roof openings ≤ 1.00 m² unbreakable and non-sliding</p> <p style="text-align: right;">supply and mounting</p>		
5		<p>pc. fall protection from roof openings ≥ 1.00 m² dimensions: m x m, unbreakable and non-sliding</p> <p style="text-align: right;">supply and mounting</p>		
6		<p>pc. steel tube stanchion with hard eyes for fixing construction of the roping protection, tested as per regulations of German employer's liability insurance association, system for mm height above fixing surface, delivery and fixing according to the installation instructions of the manufacturer and the instructions of the construction supervisor at least 2.50 m from the edge of the drop to the following:</p> <p><input type="checkbox"/> available concrete decking <input type="checkbox"/> prefabricated concrete components <input type="checkbox"/> steel structures <input type="checkbox"/> wooden trusses <input type="checkbox"/></p>		
7		<p>m safety rope, tested as per regulations of German employer's liability insurance association, as a guide rope with spliced spring hooks, delivery with manufacturer's installation instructions and handing over to construction supervisor</p>		
8		<p>pc. personal protection equipment tested as per regulations of German employer's liability insurance association, delivery with fixing rope and handing over to construction supervisor</p>		
9		<p>pc. storage box for the safety rope and for the personal protection equipment, supply and handing over to the construction supervisor</p>		
10		<p>m side protection (e.g. for work at the edge of roofs with a drop of over 3.00 m) as per DIN 4420 "Working and Safety Scaffolding", assembly and disassembly, maintaining in place for the duration of the work with FischerTRAPEZ- profiles, fixing to available arrangements provided by the customer.</p>		

Please tick as appropriate

Enquiry Form: Safety Devices for Roof Assemblies

Item	No.	Description	Price/Unit Euro	Total Euro
11		m side protection as previously described item, provided per week longer than the arranged time		
12		m side protection system (e.g. for work at the edge of roofs with a drop of over 3.00 m) according to the manufacturer's instructions for assembly and use, assembly and disassembly, maintaining in place for the duration of the work with trapezoidal roof profiles, fixing to available arrangements provided by the customer.		
13		m side protection system as previously described item, provided per week longer than the arranged time		
14		m² standing scaffolding as fall-breaker (for work on roofs with a drop of over 3.00 m an up to and including a pitch of 20°) <input type="checkbox"/> system scaffolding as per DIN 4420, system <input type="checkbox"/> steel tube coupling scaffolding as per DIN 4420 <input type="checkbox"/> ladder scaffold as per DIN 4420 scaffolding group 2 as per DIN 4420 cover width at least 0.90 m, with side protection and anchoring to load-bearing horizontal standing surface <input type="checkbox"/> horizontal standing surface <input type="checkbox"/> degree pitch standing surface assembly and disassembly, maintaining in place for the duration of the work with FischerTRAPEZ-profiles. The covering parts must correspond to the „Principles for the examination of covering parts in safety scaffolding and safety scaffolding for roofs and protective wall in safety scaffolding for roofs“ (ZH 1 /585). The distance (in height) between the edge of the drop and the fall-breaking surface may not be greater than 2.00 m. Height of the standing surface of the scaffolding above the ground floor m		
15		m² scaffolding as previously described item, provided per week longer than the arranged time		
16		m conversion of working scaffolding to fall-breaking scaffolding (for work on roofs with a drop of over 3.00 m an up to and including a pitch of 20°). Conversion of top layer of available working scaffolding to fall-breaking scaffolding as per DIN 4420 „Working and Safety Scaffolding“ through the addition of appropriate covering extensions and covering parts up to a covering width of 0.90 m and the provision of these for the duration of the work with FischerTRAPEZ-profiles for roofs and their subsequent removal. The covering parts must correspond to the „Principles for the examination of covering parts in safety scaffolding and safety scaffolding for roofs and protective wall in safety scaffolding for roofs“ (ZH 1 /585). The distance (in height) between the edge of the drop and the fall-breaking surface may not be greater than 2.00 m.		
17		m construction of fall-breaking scaffolding as previously described item, provided per week longer than the arranged time		
18		pc. ascension for reaching the workplace at a height of m as stairway, effective width m, projecting scaffolding sections with interior ladders, provision for the duration of the work and subsequent removal.		
19		pc. ascension as previously described item, provided per week longer than the arranged time		
Net total + VAT				

A large, empty rectangular box with a thin black border, intended for the user to provide details for the enquiry form.